



4460 S WINDERMERE ST
 ENGLEWOOD, CO 80110
 P: 303.761.3058
 F: 303.783.9014
 W: CHIMFG.COM
 E: CHIMFG@AOL.COM



ATD WITH DAMPER

ORDER SIZE	ATD WITH DAMPER		
A	B	C	D
6"	8.5"	1.4	26
7"	8.5"	1.9	26
8"	8.5"	2	26
9"	8.5"	2.3	26
10"	10.25"	2.4	26
12"	10.25"	3.4	26
14"	10.25"	5.1	24
16"	12"	5.3	24
18"	12"	5.6	24
20"	12"	6	24

A=Size
 B=Length
 C=Weight
 D=Gauge

CONSTRUCTED:

Hot Dipped Galvanized Steel PER ASTM A653 CS Type B

APPLICATIONS:

Commercial designed to meet SMACNA Duct Construction Standards. Maximum W.G. is positive 2" - 3".

DESCRIPTION:

All Spins are made with the finest G60 American Steel. Pop riveted seams. The collar is crimped and a deeper bead for faster installation. The conical shape allows for greater air flow.

DAMPERS:

26 GAUGE - 1 SPRING/SOLID BEARING, 1 HANDLE, 2 WING NUTS

UNION MADE IN THE UNITED STATES OF AMERICA
 PROUDLY USING 100% AMERICAN MADE METALS MANUFACTURED BY LUKJAN