



4460 S WINDERMERE ST
 ENGLEWOOD, CO 80110
 P: 303.761.3058
 F: 303.783.9014
 W: CHIMFG.COM
 E: CHIMFG@AOL.COM



ADJ. COMMERCIAL ELBOWS

ORDER SIZE	A	B	C/D
3"	0.6	26	C
4"	0.7	26	C
5"	2 / 1.0	24 / 26	C
6"	2 / 1.3	24 / 26	C
7"	1.6	26	D
8"	3.5 / 1.8	24 / 26	C
9"	2.4	26	D
10"	4.6 / 3.8	24 / 26	D
12"	5.2 / 4	24 / 26	D
14"	6.2 / 5	24 / 26	D
16"	8 / 6.3	24 / 26	D
18"	10.6	24	D
20"	11.9	24	D
22"	12.9	24	D
24"	14	24	D

A=Weight
 B=Gauge
 C=Stitched Welded
 D=Pop Rivet

CONSTRUCTED:

Hot Dipped Galvanized Steel PER ASTM A653 CS Type B

APPLICATIONS:

Commercial designed to meet SMACNA Duct Construction Standards. Maximum W.G. is 2" - 3".

DESCRIPTION:

All Adjustable Elbows are made with the finest G60 American Steel. Pop riveted and stitched welded seam on certain sizes for a more airtight and durable fitting. 5 gore construction with adjustable gores for any angle possible.

UNION MADE IN THE UNITED STATES OF AMERICA
 PROUDLY USING 100% AMERICAN MADE METALS MANUFACTURED BY LUKJAN