



4460 S WINDERMERE ST
 ENGLEWOOD, CO 80110
 P: 303.761.3058
 F: 303.783.9014
 W: CHIMFG.COM
 E: CHIMFG@AOL.COM



HETO WITHOUT DAMPER

| HETO WITHOUT DAMPER | | | | | |
|---------------------|-----|-----|-----|-----|----|
| ORDER SIZE | A | B | C | D | E |
| 4" | 10" | 5" | 1.2 | 9" | 26 |
| 5" | 10" | 6" | 1.2 | 9" | 26 |
| 6" | 12" | 6" | 1.3 | 9" | 26 |
| 7" | 11" | 5" | 1.7 | 10" | 26 |
| 8" | 12" | 6" | 1.7 | 9" | 26 |
| 9" | 14" | 6" | 1.9 | 10" | 26 |
| 10" | 14" | 7" | 2.6 | 11" | 26 |
| 12" | 14" | 8" | 3.1 | 11" | 26 |
| 14" | 14" | 9" | 3.4 | 11" | 26 |
| 16" | 14" | 12" | 4.7 | 14" | 24 |
| 18" | 14" | 14" | 5.9 | 14" | 24 |
| 20" | 14" | 14" | 8.2 | 14" | 24 |

A=Width
 B=Depth
 C=Weight
 D=Length (from bead to flange out)
 E=Gauge

CONSTRUCTED:

Hot Dipped Galvanized Steel PER ASTM A653 CS Type B

APPLICATIONS:

Commercial designed to meet SMACNA Duct Construction Standards. Maximum W.G. is 2"- 4".

DESCRIPTION:

All HETO'S are made with the finest G60 American Steel. Pop riveted seams. The collar is crimped the square side has 1" flange out with gasket for a sealed connection and faster installation times. It's 45° angle allows for better air flow.

DAMPER: 26 GAUGE - 1 SPRING/SOLID BEARING, 1 HANDLE, 2 WING NUTS

UNION MADE IN THE UNITED STATES OF AMERICA
 PROUDLY USING 100% AMERICAN MADE METALS MANUFACTURED BY LUKJAN