



4460 S WINDERMERE ST
 ENGLEWOOD, CO 80110
 P: 303.761.3058
 F: 303.783.9014
 W: CHIMFG.COM
 E: CHIMFG@AOL.COM



SLEEVED DAMPER

ORDER SIZE	A	B	C
4"	4.5"	0.6	26
5"	4.5"	0.75	26
6"	4.5"	1.2	26
7"	7.5"	1.05	26
8"	7.5"	1.44	26
10"	9.5"	2.35	26
12"	9.5"	2.96	26
14"	9.5"	3.56	26
16"	9.5"	4.1	26
18"	9.5"	4.7	26
20"	9.5"	5.5	26

A=Length
 B=Weight
 C=Gauge

CONSTRUCTED:

Hot Dipped Galvanized Steel PER ASTM A653 CS Type B

APPLICATIONS:

Commercial designed to meet SMACNA Duct Construction Standards. Maximum W.G. is 2" - 3".

DESCRIPTION:

All Sleeved Dampers are made with the finest G60 American Steel. One end is crimped and the other is raw for faster installation times for a damper. It allows you to regulate the airflow going to the end of your run out.

DAMPER:

26 GAUGE - 1 SPRING BEARING, 1 SOLID BEARING, 1 HANDLE, 2 WING NUTS

UNION MADE IN THE UNITED STATES OF AMERICA
 PROUDLY USING 100% AMERICAN MADE METALS MANUFACTURED BY LUKJAN